REGON: 521473146

NIP: 7952568415



KAWMET.PL

## DECLARATION OF PERFORMANCE NO. NR P7 PB-10,5/03/2022 IN ACCORDANCE WITH THE REGULATION UE 305/2011



1	Unique identification code of the product type	KAWMET P7 PB (10,5 kW) ECO
2	Intended use of the product	Room heater burning solid fuel without hot water supply
3	Name and address of the manufacturer	ODLEWNIA KAW-MET MAREK KAWIŃSKI Sp.z o.o. Zadąbrowie 311, 37-716, Orły, Polska
4	Name and address of the authorized representative	N/A
5	System of AVCP	System 3
6	Name and identification number of the notified body	OIL AND GAS INSTITUTE- National Research Institute, 25a Lubicz Str. 31-503 Cracow, POLAND / Notified body No. 1450
	Test report no.	3210 A5 16 / 3210 B5 16

7 DECLARED PERFORMANCE		
ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONIZED TECHNICAL SPECIFICATION
Fire safety:		
Reaction to fire	A1	
Distance to combustible materials	Minimum distances (mm): Floor = 0 Front, rear, sides, ceiling = 1500 • Combustable materiels inside the surround must be covered by insulation as decribed in the manual	EN 13240:2001 EN 13240:2001/AC:2006 EN 13240:2001/A2:2004 EN 13240:2001/A2:2004/ AC: 2007
Risk of burning fuel falling out	Pass	
Safety of filling the device with fuel	Pass	
Equipping the product with adjustable and properly marked combustion air setting devices	Pass	
Cleanability	Pass	
Correct and effective operation of the device	Pass	
Release of dangerous substances	NPD	
Electrical safety	NPD	
Nominal heat output	10,5 kW	
Room heating output	10,5 kW	
Water heating output	NPD	
Energy efficiency (η <sub>th,nom</sub> )	73,5 %	
Emission of combustion products, CO (13% O <sub>2</sub> )	0,14% / 1740 mg/m³	
Flammability	0,83 h	
Surface temperature	Manipulation handles: Primary air adjustment handle: 70,2°C Furnace door handle: 121,0 °C Ash pan door handle: 93,5 °C Secondary air adjustment handle: 145,9 °C  * The manufacturer provides tools to ensure safe operation of the device	
Flue gas temperature at nominal heat output	369,7 °C	
Maximum operating pressure	NPD	
Mechanical resistance	NPD	
Fuel type	Hardwood (moisture ≤20%)	USER MANUAL

The performance of the product identified in point 1 in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. in accordance with the regulation UE 305/2011

ODLEWNIA "KAW-MET"

MAREK KAWIŃSKI SP. Z O.O.

37-716 Orły, Zadąbrowie 311

NIP 7952568415, REGON 521473146

- John - -